

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PROVERO

Supplier's address: -

Model identifier: ID-1150

Type of light source:

| | | | |
|---|------------|---------------------------------|----------------------------|
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | INTEGRATED | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | Yes |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | Yes | Dimmable: | Only with specific dimmers |

Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|



General product parameters:

| | | | |
|--|------------------------|--|------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 2 | Energy efficiency class | G |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 27 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 889 |
| On-mode power (P_{on}), expressed in W | 2,0 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | 0,00 | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 83 |
| Outer dimensions | Height | Spectral power distribution in the | See image in last page |
| | Width | | |

| | | | | |
|---|-------|------|--------------------------------------|----------------|
| without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) | Depth | 30 | range 250 nm to 800 nm, at full-load | |
| Claim of equivalent power ^(a) | | - | If yes, equivalent power (W) | - |
| | | | Chromaticity coordinates (x and y) | 0,445 0,408 |
| Parameters for LED and OLED light sources: | | | | |
| R9 colour rendering index value | | 0 | Survival factor | 1,00 |
| the lumen maintenance factor | | 0,97 | | |

(a) : not applicable;

(b) : not applicable;



Photometric Parameters

Luminous Flux: 26.933 lm
Total mains efficacy: 15.57 lm/W

Efficiency: 15.57 lm/W
Energy Efficiency Class: G (EU 2019/2015)

Radiant Power: 89.0 mW

Electric Parameters

Voltage: 242.40V
Power Factor: 0.3620

Current: 0.0200A
Frequency: 49.99Hz

Power: 1.73W